



17"

Web : ice-tyres.com
Email : ice-tyres@orange.fr

Winter 25/26 v7.2

L	H	Ø	Profile	Hauteur clous	Qty studs	Ø without studs mm	Ø standard
195	40	17	MS Snow	1,8 - 2,2 - 2,7 - 3,5mm	295	+16mm	588-596
			MS15				
			MS12R	2,2 - 2,7 - 3,5 - 4,0mm	341	+16mm	
205	40	17	MS Snow	1,8 - 2,2 - 2,7 - 3,5mm	299	+16mm	596-604
			MS15				
			MS12R	2,2 - 2,7 - 3,5 - 4,0mm	403	+16mm	
205	45	17	MS Snow	1,8 - 2,2 - 2,7 - 3,5mm	310	+16mm	616-624
			MS15				
			MS12R	2,2 - 2,7 - 3,5 - 4,0mm	417	+16mm	
205	50	17	MS Snow	1,8 - 2,2 - 2,7 - 3,5mm	320	+16mm	637-645
			MS15				
			MS12R	2,2 - 2,7 - 3,5 - 4,0mm	431	+16mm	
215	45	17	MS Snow	1,8 - 2,2 - 2,7 - 3,5mm	314	+16mm	625-635
			MS15				
			MS12R	2,2 - 2,7 - 3,5 - 4,0mm	423	+16mm	
225	45	17	MS Snow	1,8 - 2,2 - 2,7 - 3,5mm	319	+16mm	634-644
			MS15	2,2 - 2,7 - 3,5mm	368	+22mm	
			MS12R	2,2 - 2,7 - 3,5 - 4,0mm	491	+16mm	
245	40	17	MS Snow	1,8 - 2,2 - 2,7 - 3,5mm	316	+16mm	628-638
			MS15	2,2 - 2,7 - 3,5mm	425	+22mm	
			MS12R	2,2 - 2,7 - 3,5 - 4,0mm	485	+16mm	
255	40	17	MS Snow	1,8 - 2,2 - 2,7 - 3,5mm	320	+16mm	636-646
			MS15	2,2 - 2,7 - 3,5mm	430	+22mm	
			MS12R	2,2 - 2,7 - 3,5 - 4,0mm	492	+16mm	
Standard number of studs, it's possible to reduce the quantity for the three designs — For the MS12R design, it's possible to increase the quantity of studs by up to 30%.							
215	45	17	A-Ice	1,8 - 2,5mm	378	626	625-635
225	50	17	Nica	1,8mm	540	657	637-645
225	50	17	Nica	2,5mm	420	657	637-645
225	45	17	B-Ice	1,8 - 2,5mm	400	650	634-644